



OFFICE OF THE
STATE POLLUTION CONTROL BOARD, ODISHA

Parivesh Bhawan, A/118, Nilakantha Nagar, Unit-VIII,
Bhubaneswar - 751 012

BY REGD POST

No. 2372 /

Ind-II-NOC-5919

Date 10.02.2015

OFFICE MEMORANDUM

In consideration of the application for obtaining Consent to Establish for **Samaleswari OCP of M/s. Mahanadi Coalfields Ltd.**, the State Pollution Control Board has been pleased to convey its Consent to Establish under section 25 of Water (Prevention & Control of Pollution) Act, 1974 and section 21 of Air (Prevention & Control of Pollution) Act, 1981 for enhancement of production capacity of Coal from 11.0 MTPA to 15.0 MTPA (over mine lease hold area of 828.76 ha + 99.5 ha. and 49.855 ha. for colony outside the mining lease), At – IB Valley Area, P.O. - Rampur Colliery, Brajarajnagar of Jharsuguda District with the following conditions.

GENERAL CONDITIONS:

1. This Consent to establish is valid for the product, method of mining and capacity mentioned in the application form. This order is valid for five years, which means the proponent shall commence mining activities for the proposal within a period of five years from the date of issue of this consent to establish order. If the proponent fails to commence mining activities for the proposal within five years then a renewal of this consent to establish shall be sought by the proponent.
2. Adequate effluent treatment facilities are to be provided such that the quality of sewage and trade effluent satisfies the standards as prescribed under Environment Protection Rule, 1986 or as prescribed by the Central Pollution Control Board and/or State Pollution Control Board or otherwise stipulated in the special conditions.
3. All emission from the mining activities as well as the ambient air quality and noise shall conform to the standards as laid down under Environment (Protection) Act. 1986 or as prescribed by Central Pollution Control Board/State Pollution Control Board or otherwise stipulated in the special conditions.
4. Appropriate method of disposal of solid waste is to be adopted to avoid environmental pollution.
5. The mine shall comply to the provisions of Environment Protection Act, 1986 and the rules made there under with their amendments from time to time such as the Hazardous Waste (Management, Handling & Transboundary Movement) Rules 2008, Hazardous Chemical Rules / Manufacture, Storage and Import of Hazardous Chemical Rules, 1989 etc. and amendments there under. The mine shall also comply to the provisions of Public Liability Insurance Act, 1991, if applicable.
6. The mine shall apply for grant of Consent to operate under section 25/26 of Water(Prevention & Control of Pollution) Act, 1974 & Air (Prevention & Control of Pollution) Act, 1981 at least 3

(three) months before the commencement of production and obtain Consent to Operate from this Board.

7. **This consent to establish is subject to statutory and other clearances from Govt. of Odisha and/or Govt. of India, as and when applicable.**

SPECIAL CONDITIONS:

1. **The proponent shall comply to the conditions imposed in environmental clearance issued by MoEF, Govt. of India vide letter No. J-11015/183/2008-IA.II (M) dated 06.02.2015.**
2. The mine should not store for more than seven days of coal production to avoid coal fire in stock yard as well as coal seam. The mine shall take adequate preventive measures for spontaneous fire in the coal seam as well as stock yard and an action plan regarding this shall be submitted at the time of consent to operate application.
3. The mine shall use surface miner instead of sovel dumper for mining activity. No change in mining technology and scope of working shall be made without prior approval of the Board.
4. Top soil should be stacked separately with proper slope at earmarked site(s) with adequate measures and shall be used for reclamation and rehabilitation of mined out areas.
5. **Back filling of abandoned pit shall be carried out as per approved mining plan. Monitoring and management of rehabilitated areas should continue until the vegetation becomes self-sustaining. Compliance status in this regard shall be submitted to the Board on yearly basis.** The mine shall explore the possibility for back filling of mine voids by fly ash generation from nearby thermal power plant.
6. Garland drains (size, gradient and length) and sump capacity shall be designed keeping 50% safety margin over and above the hourly peak rain fall and maximum discharge in the area adjoining the mine site. Sump capacity should have adequate retention period to allow proper settling of silt material.
7. Dimension of the retaining wall at the toe of dumps and OB benches within the mine to check run-off and siltation shall be based on the rainfall data. The detail specification shall be worked out and submitted to the Board.
8. Catch drains of appropriate size should be constructed to divert the run off from the OB dump to the siltation pond of appropriate size to arrest silt and sediment flows from soil, OB and mineral dumps. Similar arrangement shall be done around the coal stack pile area. The drains should be regularly desilted and maintained properly. Surface run-off from OB dump area, coal pile area, top soil storage area shall be routed through adequate settling pond (designed maximum hourly rain fall basis) to meet prescribed standard of **SS-50 mg/l and Oil & Grease-5 mg/l** before discharge into natural stream/water courses during monsoon.
9. Regular monitoring of ground water level and quality should be carried out by establishing a network of existing wells. The monitoring should be done four times a year in pre-monsoon (April/May), monsoon (August), Post – monsoon (November) and winter (January) seasons. Data thus collected should be submitted to the Board quarterly.

10. Sewage Treatment Plant should be installed for the treatment of domestic effluent generated from the colony and mines so as to meet the prescribed standard such as **pH = 5.5 - 9.0, SS = 50 mg/l, BOD = 30 mg/l & O&G = 5 mg/l** and shall be reused for green belt development.
11. Wastewater (workshop) shall be properly collected, treated in ETP consists of primary settling tank, O&G trap, flash mixer with chemical dosing and secondary settling tank so as to conform the prescribed standard **pH = 5.5 - 9.0, SS = 50 mg/l, O&G = 5 mg/l** or as amended from time to time and reused for washing with make-up water.
12. Mine drainage water, shall be treated properly in adequate size of settling tanks with coagulation and chemical dosing facilities. The mine shall explore to reuse it for dust suppression, green belt and vehicle washing. Balance treated mine drainage water shall be discharged to sewer or land or stream then the effluent shall conform to standard prescribed by the Board i.e. **pH = 5.5 to 9.0, total SS = 50 mg/l (during non-rainy day) & 100 mg/l (during rainy day), O&G = 5 mg/l (during non-rainy day) & 10 mg/l (during rainy day)** and other parameters conforming to standards for discharge to inland surface water as prescribed under EP Act, 1986.
13. Rain water harvesting practice shall be followed by utilizing the rain water collected from the roof of the buildings for recharging of ground water within the premises and other large structures as per the concept and practices prescribed by CPCB, New Delhi and details of which is available in the web site.
14. **Crushers at the CHP** of adequate capacity for the expansion project shall be operated with high efficiency bag filters. Water sprinkling systems shall be provided to check fugitive emissions from crushing operations, conveyor system, haulage roads, transfer points etc. **Provision of movable chutes shall be made during loading at CHP to avoid free fall of coal.**
15. Water sprinkling shall be carried out on unplanted surface of OB dump to control fugitive emission.
16. Drilling shall be avoided to the maximum possible extent. However, drill should be wet operated or with dust extractors and controlled blasting should be practiced.
17. The mine shall provide water or water mixed chemicals for dust suppression at all strategic points such as coal stack yards, loading and unloading points, all transfer points, conveyors etc. to suppress dust fine atomizer nozzles arrangement shall be provided on the coal heaps and on land around the crusher / pulverizes. As far as possible conveyors and transfer points etc. shall be provided with enclosures.
18. **Six (6) ambient air quality monitoring stations** for 24 hours operation should be established in the core zone as well as in the buffer zone for PM₁₀, PM_{2.5}, SO₂, NO_x, and CO monitoring. Location of the stations should be decided based on the metrological data, topographical features and environmentally and ecologically sensitive targets in consultation with the State Pollution Control Board.
19. Data on ambient air quality (PM₁₀, PM_{2.5}, SO₂, NO_x and CO) shall be regularly submitted to the State Pollution Control Board once in six months.
20. **The mine has to comply the following standard at the loading or unloading, haul road, coal transportation road, coal handling plant(CHP), railway siding, blasting, drilling,**

overburden dumps or any other dust generating external sources as per the Rule2(1) of the Environmental Amendment Rules, 2000 notified vide notification G.S.R. 742(E), dated 25.09.2000.

Pollutant	Time weighted average	Concentration in Ambient Air	Method of Measurement
1	2	3	4
SPM	Annual Average*	360 $\mu\text{g}/\text{m}^3$	High volume sampling (Average flow rate not less than 1.1m ³ /min)
	24 hours**	500 $\mu\text{g}/\text{m}^3$	
RPM(size less than 10 μm)	Annual Average*	180 $\mu\text{g}/\text{m}^3$	Respirable Particulate matter sampling and analysis
	24 hours**	250 $\mu\text{g}/\text{m}^3$	
SO ₂	Annual Average*	80 $\mu\text{g}/\text{m}^3$	Improved west and Gaeke method Ultraviolet flu0rescence
	24 hours**	120 $\mu\text{g}/\text{m}^3$	
NO ₂	Annual Average*	80 $\mu\text{g}/\text{m}^3$	Jacob & Hochheiser Modified (Na-Arsenic) Method Gas phase Chemiluminescence
	24 hours**	120 $\mu\text{g}/\text{m}^3$	

(*Annual Arithmetic mean for the measurements taken in a year, following the guidelines for frequency of sampling laid down in clause2.

**24 hourly/ 8 hourly values shall be met 92% of the time in a year. However, 80% of the time may exceed but not on two consecutive days.)

21. The haul roads and arterial roads shall be made black topped / concrete with avenue plantation.
22. A green belt of adequate width and density preferably with local species along the periphery of the mine, inactive dumps, backfilled area, vacant area, colony and any other vacant area shall be raised so as to provide protection against particulates and noise to ameliorate the environment. A detailed plantation programme in this regard shall be prepared and submitted at the time of making application for consent to operate for assessment.
23. Adequate measures shall be taken for control of noise levels below 85 dB (A) in the work environment.
24. Environmental laboratory should be established with adequate number and type of pollution monitoring and analysis equipment in consultation with the State Pollution Control Board.
25. A separate environmental management cell with suitable qualified personnel should be set up under the control of a Senior Executive, who will report directly to the Head of the organization.
26. All efforts shall be taken to protect the existing water bodies in the surrounding. A definite plan in this regard shall be submitted to the Board within 06 months from the date of issue of this order.
27. The Board may impose further condition or modify the conditions stipulated in this order during installation, and / or at the time of obtaining consent to operate and may revoke this clearance in case the stipulated conditions are not implemented and / or any information suppressed in the application form.

28. The above conditions will be enforced, inter-alia, under the provisions of the Water (Prevention & Control of Pollution) Act, 1974 the Air (Prevention & Control of Pollution) Act, 1981 the Environment (Protection) Act, 1986 and the Public Liability Insurance Act, 1991 along with their amendments and rules.

To,

The Project Officer,
Samaleswari OCP of
M/s Mahanadi Coalfields Ltd.,
At- Hill Top Colony,
Post - Rampur Colliery, Brajarajnagar,
Dist - Jharsuguda - 768225
Odisha


MEMBER SECRETARY

Memo No. _____ /Dt. _____ /

Copy forwarded to:

1. The Secretary Steels & Mines, Govt. of Odisha, Bhubaneswar
2. The District Magistrate & Collector, **Jharsuguda**.
3. The Director, Directorate of Mines, Govt. of Odisha, Bhubaneswar
4. The Regional Officer, SPC Board, Sambalpur.
5. The DFO, **Jharsuguda**.
6. Copy to HSM Cell, SPC Board, Bhubaneswar
7. Consent to operate section, SPC Board, Bhubaneswar.
8. Copy to Guard file


SR. ENV. ENGINEER (N)