



BY REGD. POST WITH AD

#### STATE POLLUTION CONTROL BOARD, ODISHA

A/118, Nilakantha Nagar, Unit-VIII, Bhubaneswar-751012
Phone-2561909, Fax: 2562822, 2560955 E-mail: paribesh1@ospcboard.org, Website: www.ospcboard.org

#### **CONSENT ORDER**

No. 2525 / IND-I-CON-1217 Dt. 22-02-17.

#### **CONSENT ORDER NO. 504**

Sub: Consent for discharge of sewage and trade effluent under section 25/26 of Water (PCP) Act, 1974 and for existing / new operation of the plant under section 21 of Air (PCP) Act, 1981.

Ref: Your online application No. 1447958 Dated 17.12.2016

Consent to operate is hereby granted under section 25/26 of Water (Prevention & Control of Pollution) Act, 1974 and under section 21 of Air (Prevention & Control of Pollution) Act, 1981 and rules framed thereunder to

Name of the Industry: ANANTA OPEN CAST PROJECT OF M/S. MCL

Name of the Occupier & Designation: ARUN M. LAKHE, PROJECT OFFICER

Address: At/PO: DERA, DIST - ANGUL, PIN: 759103.

This consent order is valid for the period up to 31.03.2018

This consent order supersedes the earlier consent order issued vide Board's letter No. 2149 dated 01.02.2016.

#### **Details of Products Manufactured**

SI. No.	Product	Quantity
1.	Coal	12 MTPA

This consent order is valid for the specified outlets, discharge quantity and quality, specified chimney/stack, emission quantity and quality of emissions as specified below. This consent is granted subject to the general and special conditions stipulated therein.



#### A. Discharge permitted through the following outlet subject to the standard

	Description of outlet	The same of the sa	Quantity	Pre-	Pre-s	scribed Standard			
t No.	orounet	discharge	of discharge KL/hr	рН		Fecal Coliform (MPN/10 0ml)	BOD (mg/l)	COD (mg/l)	
01	STP outlet (Domestic effluent)	On land for irrigation after treatment in STP	32.5	6.5-9.0	10	<230	10	50	

# B. Emission permitted through the following stack subject to the prescribed standard

Chimney Stack No.	Description of Stack	Stack height (m)	Quantity of emission	Prescribed Standard			
				PM (mg/Nm³)	SO <sub>2</sub>	NO <sub>x</sub>	
01.							

C. Disposal of solid waste permitted in the following manner

SI. No.	Type of Solid waste	Quantity generated (TPD)	Quantity to be reused on site(TPD)	Quantity to be reused off site(TPD)	Quantity disposed off (TPD)	Description of disposal site.
01	Top Soil/overbu rden	As per approved mining plan				As per approved mining plan



#### CONSENT ORDER

#### ANANTA OPEN CAST PROJECT OF M/S. MCL.

#### D. GENERAL CONDITIONS FOR ALL UNITS

- 1. The consent is given by the Board in consideration of the particulars given in the application. Any change or alternation or deviation made in actual practice from the particulars furnished in the application will also be the ground liable for review/variation/revocation of the consent order under section 27 of the Act of Water (Prevention & Control of Pollution) Act, 1974 and section 21 of Air (Prevention & Control of Pollution) Act, 1981 and to make such variations as deemed fit for the purpose of the Acts.
- 2. The industry would immediately submit revised application for consent to operate to this Board in the event of any change in the quantity and quality of raw material / and products / manufacturing process or quantity /quality of the effluent rate of emission / air pollution control equipment / system etc.
- The applicant shall not change or alter either the quality or quantity or the rate of discharge or temperature or the route of discharge without
  the previous written permission of the Board.
- 4. The application shall comply with and carry out the directives/orders issued by the Board in this consent order and at all subsequent times without any negligence on his part. In case of non-compliance of any order/directives issued at any time and/or violation of the terms and conditions of this consent order, the applicant shall be liable for legal action as per the provisions of the Law/Act.
- 5. The applicant shall make an application for grant of fresh consent at least 90 days before the date of expiry of this consent order.
- 6. The issuance of this consent does not convey any property right in either real or personal property or any exclusive privileges nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of Central, State laws or regulation.
- 7. This consent does not authorize or approve the construction of any physical structure or facilities or the undertaking of any work in any natural water course.
- 8. The applicant shall display this consent granted to him in a prominent place for perusal of the public and inspecting officers of this Board.
- 9. An inspection book shall be opened and made available to Board's Officers during the visit to the factory.
- 10. The applicant shall furnish to the visiting officer of the Board any information regarding the construction, installation or operation of the plant or of effluent treatment system / air pollution control system / stack monitoring system any other particulars as may be pertinent to preventing and controlling pollution of Water / Air.
- Meters must be affixed at the entrance of the water supply connection so that such meters are easily accessible for inspection and maintenance and for other purposes of the Act provided that the place where it is affixed shall in no case be at a point before which water has been taped by the consumer for utilization for any purposes whatsoever.
- 12. Separate meters with necessary pipe-line for assessing the quantity of water used for each of the purposes mentioned below:
  - a) Industrial cooling, spraying in mine pits or boiler feed,
  - b) Domestic purpose
  - c) Process
- 13. The applicant shall display suitable caution board at the lace where the effluent is entering into any water-body or any other place to be indicated by the Board, indicating therein that the area into which the effluents are being discharged is not fit for the domestic use/bathing.
- 14. Storm water shall not be allowed to mix with the trade and/or domestic effluent on the upstream of the terminal manholes where the flow measuring devices will be installed.
- The applicant shall maintain good house-keeping both within the factory and the premises. All pipes, valves, sewers and drains shall be leak-proof. Floor washing shall be admitted into the effluent collection system only and shall not be allowed to find their way in storm drains or open areas.
- 16. The applicant shall at all times maintain in good working order and operate as efficiently as possible all treatment or control facilities or systems install or used by him to achieve with the term(s) and conditions of the consent.
- 17. Care should be taken to keep the anaerobic lagoons, if any, biologically active and not utilized as mere stagnation ponds. The anaerobic lagoons should be fed with the required nutrients for effective digestion. Lagoons should be constructed with sides and bottom made impervious.
- 18. The utilization of treated effluent on factory's own land, if any, should be completed and there should be no possibility of the effluent gaining access into any drainage channel or other water courses either directly or by overflow.
- 19. The effluent disposal on land, if any, should be done without creating any nuisance to the surroundings or inundation of the lands at any time.
- 20. If at any time the disposal of treated effluent on land becomes incomplete or unsatisfactory or create any problem or becomes a matter of dispute, the industry must adopt alternate satisfactory treatment and disposal measures.
- 21. The sludge from treatment units shall be dried in sludge drying beds and the drained liquid shall be taken to equalization tank.
- 22. The effluent treatment units and disposal measures shall become operative at the time of commencement of production
- 23. The applicant shall provide port holes for sampling the emissions and access platform for carrying out stack sampling and provide electrical outlet points and other arrangements for chimneys/stacks and other sources of emissions so as to collect samples of emission by the Board or the applicant at any time in accordance with the provision of the Act or Rules made therein.



- 24. The applicant shall provide all facilities and render required assistance to the Board staff for collection of samples / stack monitoring / inspection.
- 25. The applicant shall not change or alter either the quality or quantity or rate of emission or install, replace or alter the air pollution control equipment or change the raw material or manufacturing process resulting in any change in quality and/or quantity of emissions, without the previous written permission of the Board.
- 26. No control equipments or chimney shall be altered or replaced or as the case may be erected or re-erected except with the previous approval of the Board.
- 27. The liquid effluent arising out of the operation of the air pollution control equipment shall be treated in the manner and to ion of standards prescribed by the Board in accordance with the provisions of Water (Prevention and Control of Pollution) Act, 1974 (as amended).
- 28. The stack monitoring system employed by the applicant shall be opened for inspection to this Board at any time
- 29. There shall not be any fugitive or episodal discharge from the premises.
- 30. In case of such episodal discharge/emissions the industry shall take immediate action to bring down the emission within the limits prescribed by the Board in conditions/stop the operation of the plant. Report of such accidental discharge /emission shall be brought to the notice of the Board within 24 hours of occurrence.
- 31. The applicant shall keep the premises of the industrial plant and air pollution control equipments clean and make all hoods, pipes, valves, stacks/chimneys leak proof. The air pollution control equipments, location, inspection chambers, sampling port holes shall be made easily accessible at all times.
- Any upset condition in any of the plant/plants of the factory which is likely to result in increased effluent discharge/emission of air pollutants and / or result in violation of the standards mentioned above shall be reported to the Headquarters and Regional Office of the Board by fax / speed post within 24 hours of its occurrence.
- The industry has to ensure that minimum three varieties of trees are planted at the density of not less than 1000 trees per acre. The trees may be planted along boundaries of the industries or industrial premises. This plantation is stipulated over and above the bulk plantation of trees in that area.
- The solid waste such as sweeping, wastage packages, empty containers residues, sludge including that from air pollution control equipments collected within the premises of the industrial plants shall be disposed off scientifically to the satisfaction of the Board, so as no to cause fugitive emission, dust problems through leaching etc., of any kind.
- 35. All solid wastes arising in the premises shall be properly classified and disposed off to the satisfaction of the Board by :
  - Land fill in case of inert material, care being taken to ensure that the material does not give rise to leachate which may percolate into ground water or carried away with storm run-off.
  - ii) Controlled incineration, wherever possible in case of combustible organic material.
  - iii) Composting, in case of bio-degradable material.
- Any toxic material shall be detoxicated if possible, otherwise be sealed in steel drums and buried in protected areas after obtaining approval of this Board in writing. The detoxication or sealing and burying shall be carried out in the presence of Board's authorized persons only. Letter of authorization shall be obtained for handling and disposal of hazardous wastes.
- 37. If due to any technological improvement or otherwise this Board is of opinion that all or any of the conditions referred to above requires variation (including the change of any control equipment either in whole or in part) this Board shall after giving the applicant an opportunity of being heard, vary all or any of such condition and thereupon the applicant shall be bound to comply with the conditions so varied.
- 38. The applicant, his/heirs/legal representatives or assignees shall have no claim whatsoever to the condition or renewal of this consent after the expiry period of this consent.
- 39. The Board reserves the right to review, impose additional conditions or condition, revoke change or alter the terms and conditions of this consent.
- Notwithstanding anything contained in this conditional letter of consent, the Board hereby reserves to it the right and power under section 27(2) of the Water (Prevention & Control of Pollution) Act, 1974 to review any and/or all the conditions imposed herein above and to make such variations as deemed fit for the purpose of the Act by the Board.
- 41. The conditions imposed as above shall continue to be in force until revoked under section 27(2) of the Water (Prevention & Control of Pollution) Act, 1974 and section 21 A of Air (Prevention & Control of Pollution) Act, 1981.
- 42. In case the consent fee is revised upward during this period, the industry shall pay the differential fees to the Board (for the remaining years) to keep the consent order in force. If they fail to pay the amount within the period stipulated by the Board the consent order will be revoked without prior notice.
- 43. The Board reserves the right to revoke/refuse consent to operate at any time during period for which consent is granted in case any violation is observed and to modify/ stipulate additional conditions as deemed appropriate

### GENERAL CONDITIONS FOR UNITS WITH INVESTMENT OF MORE THAN Rs 50 CRORES, AND 17 CATEGORIES OF HIGHLY POLLUTING INDUSTRIES (RED A).

 The applicant shall analyse the emissions every month for the parameters indicated in TABLE .B & C as mentioned in this order and shall furnish the report thereof to the Board by the 10<sup>th</sup> of the succeeding month.



- The applicant shall provide and maintain at his own cost three ambient air quality monitoring stations for monitoring Suspended 2 Particulate Matter, Sulphor Dioxide, Oxides of Nitrogen, Hydro-Carbon, Carbon-Monixide and monitor the same once in a day/week/fortnight/month. The data collected shall be maintained in a register and a monthly extract be furnished to the Board.
- The applicant shall provide and maintain at his own cost a meteorological station to collect the data on wind velocity, direction, temperature, humidity, rainfall, etc. and the daily reading shall be recorded and the extract sent to the Board once in a month. 3
- The applicant shall forward the following information to the Member Secretary, State Pollution Control Board, Odisha, Bhubaneswar regularly.
  - Report of analysis of stack monitoring, ambient air quality monitoring meteorological data as required every month. a.
  - h Progress on planting of trees quarterly.
- The applicant shall install mechanical composite sampling equipment and continuous flow measuring / recording devices on the effluent 5. drains of trade as well as domestic effluent. A record of daily discharge shall be maintained.
- The following information shall be forwarded to the Member Secretary on or before 10<sup>th</sup> of every month. 6
  - Performance / progress of the treatment plant.
  - a. b. Monthly statement of daily discharge of domestic and/or trade effluent.

#### Non-compliance with effluent limitations

- If for any reason the applicant does not comply with or is unable to comply with any effluent limitations specified in this consent, a) the applicant shall immediately notify the consent issuing authority by telephone and provide the consent issuing authority with the following information in writing within 5 days of such notification.
  - i) Causes of non-compliance
  - A description of the non-compliance discharge including its impact on the receiving waters
  - Anticipated time of continuance of non-compliance if expected to continue or if such condition has been corrected ii) the duration or period of non-compliance
  - (iii Steps taken by the applicant to reduce and eliminate the non-complying discharge and
  - Steps to be taken by the applicant too prevent the condition of non-compliance.
- The applicant shall take all reasonable steps to minimize any adverse impact to natural waters resulting from non-compliance b) with any effluent limitation specified in this consent including such accelerated or additional monitoring as necessary to determine the nature and impact of the non-complying discharge.
- Nothing in this consent shall be construed to relieve the applicant from civil or criminal penalties for non-compliance whether or c) not such non-compliance is due to factors beyond his control, such as break-down, electric failure, accident or natural disaster.
- The applicant shall at his own cost get the effluent samples collected both before and after treatment and get them analysed at an approval 8 laboratory every month for the parameters indicated in Part-D and shall submit in duplicate the report thereof to the Board.
- The addition of various treatment chemicals should be done only with mechanical dosers and proper equipment for regulation of correct dosages determined daily and for proper uniform feeding. Crude practices such as dumping of chemicals in drains or sumps or trickling of acids or alkalies arbitrarily and utilizing poles for stirring etc. should not be resorted to.
- In the disposal of treated effluent on land for irrigation, the industry shall keep in view of the need for; 10

Change of point of application of effluent on land

A portion of land kept fallow.

- The adoption of these would avoid soil becoming sick or slate, the industry may ensure this in consultation with the Agriculture Department. 11.
- It is the sole responsibility of the industry to ensure that there are no complaints at any time from the royats in the surrounding areas as a 12. result of discharge of sewage or trade effluent if any.
- 13. Proper house keeping shall be maintained by a dedicated team.
- The industry must constitute a team of responsible and technically qualified personnel who will ensure continuous operation of all pollution 14 control devices round the clock (including night hours) and should be in a position to explain the status of operation of the pollution control measures to the inspecting officers of the Board at any point of time. The name of these persons with their contact telephone numbers shall be intimated to the concerned. Regional Officer and Head Office of the Board and in case of any change in the team it shall be intimated to the Board immediately



#### E. SPECIAL CONDITIONS:

- 1. Excavation of coal shall be done using surface miners. The surface miner shall be operated along with dust control measures.
- Drills shall either be operated with dust extractors or equipped with water injection system to minimize dust generation in the work environment.
   Controlled blasting shall be done for removal of overburden (OB) and blasting shall be carried out during day time only.
- 3. The annual coal production and compliance status report of the stipulated conditions shall be submitted to the Board latest by 30th April every year.
- 4. The environmental statement report for the financial year ending 31st March shall be submitted to the Board in form-V on or before 30th September every year.
- 5. The surface runoff generated from the mining area as well as railway siding during monsoon shall be diverted to adequate size of sedimentation pond or mine sump for storage and use. Systems shall be in place for collection and channelizing the surface runoff to the sedimentation pond/mine sump.
- 6. Strata water generated during mining operation shall be diverted to the available sump for storage and use.
- 7. No disposal of strata water & surface runoff to outside shall be allowed under any circumstances. Zero Liquid Discharge shall be ensured.
- 8. Workshop from where water pollution due to wash out of oil and grease and suspended solids is expected, Effluent Treatment Plant (ETP) shall be provided and treated wastewater shall be reused for vehicle washing. No wastewater from workshop shall be allowed to be discharged to outside under any circumstances.



- 9. The existing Sewage Treatment Plant (STP) shall be upgraded to ensure compliance of stringent norms specified of Sl. No. A of the Consent Order.
- 10. The top soil and overburden shall be removed separately and stored it in separate heaps, duly covered with grass and vegetation or utilized for backfilling of mined out area.
- 11. Concurrent backfilling of mined out area shall be done. The backfilled area shall be technically and biologically reclaimed.
- 12. Acid mine drainage water if any, shall be treated adequately and used only for sprinkling activity.
- 13. Regular monitoring of ground water level and quality should be carried out by establishing a network of existing wells. The monitoring should be done four times a year in pre-monsoon (April/May), monsoon (August), post-monsoon (November) and winter (January) seasons. Data thus collected should be submitted to the Board quarterly.
- 14. Action shall be taken for removal of coal going along with over burden so that spontaneous fire in the dump site can be eliminated. Water sprinkling arrangements shall also be provided at the exposed coal seam faces and other vulnerable areas for control of spontaneous fire if any.
- 15. Instant water shower system at the exit point of the quarry shall be provided and all heavy vehicles loaded with coal shall move through the instant shower system. Wheel washing facility for coal transport vehicles at the exit point of the quarry or at the coal stack yard as per the requirement shall be provided.
- 16. Coal handling plant/ Crusher unit shall be operated with adequate dust extraction system or dry fog system for dust suppression. Loading, unloading areas and conveyor systems including all transfer points shall have adequate dust suppression measures.



- 17. The railway sidings shall have adequate fixed water sprinkling system for suppression of dust generated during unloading and loading activities. In addition to this, firefighting system shall be in place to control fire in the coal stack yard of railway sidings.
- 18. Coal transportation through roads shall be done in covered vehicles.
- 19. All internal coal transportation roads shall be black topped/concreted.

  Necessary dust suppression measures shall also be provided for these roads to suppress the dust generated during movement of vehicles.

  Plantation of thick leaf trees on both sides of the road shall be done.
- 20. Mobile water sprinkling shall be provided for dust suppression on the temporary quarry haul roads and sprinkling of water shall be done at desired intervals so as to prevent generation of fugitive dust.
- 21. All internal coal transportation roads, temporary mine haul roads and other material transportation roads of the mine shall be maintained properly and creation of ruts and pot holes shall be avoided.
- 22. Appropriate action shall be taken to enhance rake loading facility for coal transportation through rail.
- 23. All necessary precaution shall be taken to prevent fire in coal stack yards and coal seams. Necessary precautionary measures, inter alia, maintaining a minimum stock shall be taken to avoid fire hazards in the coal stack yard.
- 24. Ambient air quality measured at a distance of 500m from the dust generating sources {Loading or un-loading, haul road, coal transportation road, coal handling plant (CHP), Railway siding, Blasting, Drilling, overburden dumps or any other dust generating source like nearby roads etc.} in the down wind direction shall meet the following standards.



Pollutant		Concentration in µg/m³ (24 hourly value)
SPM	-	600
RPM	-	300
$SO_2$	-	120
$NO_2$	-	120

In case any residential or commercial or industrial place falls within 500 metres of any generating sources, the National Ambient Air Quality Standards for industrial area notified shall be applicable.

- 25. Continuous Ambient Air Quality Monitoring Stations (at least 04 nos. keeping in view the cumulative impact of all mines) shall be installed with data transfer facility to SPCB Server in Talcher area for monitoring of PM<sub>10</sub>, PM<sub>2.5</sub>,SO<sub>2</sub> and NO<sub>2</sub> by June-2017. The location of CAAQMS shall be finalized in consultation with the Regional Officer, State Pollution Control Board.
- 26. Adequate measures shall be taken for control of noise levels below the following limits.

- 27. Ambient air quality monitoring data, noise monitoring data and wastewater quality monitoring data shall be electronically displayed at the entry point of the mine or at a suitable location of the mine.
- 28. The mine shall take action to increase the supply of drinking water in the peripheral villages.
- 29. Plantation of trees shall be undertaken in the colony/ township, over top soil dumps, OB dumps, back filled areas, along the side of haul road and in other areas of the mines not being utilized for mining activities. The mine shall take up avenue plantation and plantation in nearby village areas in



consultation with DFO/Horticulture Department. The plantation details shall be submitted to the Board before end of March every year.

- 30. Mining operation is subject to availability of all other statutory clearances.
- 31. The mine shall submit a declaration by 30th of April every year that all pollution control systems are in good condition, operated and ambient air quality as well as wastewater quality conforms to the prescribed standards.

MEMBER SECRETARY
STATE POLLUTION CONTROL BOARD, ODISHA

To,

ARUN M. LAKHE, PROJECT OFFICER, ANANTA OPEN CAST PROJECT OF M/S. MCL, PO: DERA, DIST: ANGUL, PIN-759103.

Memo No	)/Dt. /
Copy f	orwarded to :
i)	Regional Officer, State Pollution Control Board, Angul.
ii)	District Collector, Angul
iii)	Director of Mines, Govt. of Odisha, Bhubaneswar
iv)	Director, Environment-cum-Special Secretary, F & E. Dept. Govt. of Odisha
	Bhubaneswar
V)	D.F.O , <u>Angul</u>
vi)	Deputy Director of Mines, Talcher
vii)	Sr. Env. Engineer-L-I (C) (Hazardous waste cell)
viii)	Sr. Env. Scientist –L-I (L), Central Lab. SPCB, Bhubaneswar
ix)	Cess Section (Head Office)
x)	Consent Register

SR. ENV. SCIENTIST (MINES)
STATE POLLUTION CONTROL BOARD, ODISHA



# GENERAL STANDARDS FOR DISCHARGE OF ENVIRONMENTAL POLLUTANTS



# GENERAL STANDARDS FOR DISCHARGE OF ENVIRONMENTAL POLLUTANTS PART -A: EFFLUENTS

SI.No.	Parameters	Standards						
		Inland surface	Public sewers	Land for irrigation	Marine Costal Areas			
		(a)	(b)	(c)	(d)			
1.	Colour & odour	Colourless/Odou rless as far as practible		See 6 of Annex-1	See 6 of Annex-1			
2.	Suspended Solids (mg/l)	100	600	200	For process wastewater – 100 b. For cooling water effluent 10% above total suspended matter of influent.			
3.	Particular size of SS	Shall pass 850						
5.	pH value	5.5 to 9.0	5.5 to 9.0	5.5 to 9.0	5.5 to 9.0			
6.	Temperature	Shall not exceed 5°C above the receiving water temperature			Shall not exceed 5°C above the receiving water temperature			
7.	Oil & Grease mg/l max.	10	20	10	20			
8.	Total residual chlorine	1.0			1.0			
9.	Ammonical nitrogen (as N) mg/l max.	50	50		50			
10.	Total Kajeldahl nitrogen (as NH <sub>3</sub> ) mg/1 max.	100			100			
11.	Free ammonia (as NH <sub>3</sub> ) mg/1 max.	5.0			5.0			
12.	Biochemical Oxygen Demand (5 days at (20°C) mg/1 max.	30	350	100	100			
13.	Chemical Oxygen Demand, mg/1 max.	250			250			
14.	Arsenic (as As) mg/1 max.	0.2	0.2	0.2	0.2			
15.	Mercury (as Hg) mg/1 max.	0.01	0.01		0.001			
16.	Lead (as pb) mg/1 max.	01.	1.0		2.0			



17.	Cardmium (as Cd) mg/1 max.	2.0	1.0		2.0
18.	Hexavalent Chromium (as Cr + 6) mg/l max.	0.1	2.0		1.0
19.	Total Chromium (as Cr) mg/l max.	2.0	2.0		2.0
20.	Copper (as Cu) mg/l max.	3.0	3.0		3.0
21.	Zinc (as Zn) mg/l max.	5.0	15		15
22.	Selenium (as Sc) mg/l max.	0.05	0.05		0.05
23.	Nickel (as Nil) mg/l max.	3.0	3.0		5.0
24.	Cyanide (as CN) mg/l max.	0.2	2.0	0.2	0.02
25.	Fluoride ( as F) mg/l max.	2.0	15		15
26.	Dissolved Phosphates (as P) mg/l max.	5.0			
27.	Sulphide (as S) mg/l max.	2.0			5.0
28.	Phennolic compounds as (C <sub>6</sub> H <sub>5</sub> OH) mg/l max.	1.0	5.0		5.0
29.	Radioactive materials a. Alpha emitter micro curle/ml.	10 <sup>7</sup>	10 <sup>7</sup>	10 <sup>8</sup>	10 <sup>7</sup>
	b. Beta emitter micro curle/ml.	10 <sup>6</sup>	10 <sup>6</sup>	10 <sup>7</sup>	10 <sup>6</sup>
30.	Bio-assay test	90% survival of fish after 96 hours in 100% effluent	90% survival of fish after 96 hours in 100% effluent	90% survival of fish after 96 hours in 100% effluent	90% survival of fish after 96 hours in 100% effluent
31	Manganese (as Mn)	2 mg/l	2 mg/l		2 mg/l
32.	Iron (Fe)	3 mg/i	3 mg/l		3 mg/l
33.	Vanadium (as V)	0.2 mg/l	0.2 mg/l		0.2 mg/l
34.	Nitrate Nitrogen	10 mg/l			20 mg/l



#### NATIONAL AMBIENT AIR QUALITY STANDARDS

Sl. No.	Pollutants	Time Weighed	Concentrate of Ambient Air				
		Average	Industrial Residential, Rural and other Area	Ecologically Sensitive Area (notified by Central Government)	Methods of Measurement		
(1)	(2)	(3)	(4)	(5)	(6)		
1.	Sulphur Dioxide (SO <sub>2</sub> ), μg/m <sup>3</sup>	Annual *	50	20	-Improved west and Gaeke		
		24 Hours **	80	80	- Ultraviolet fluorescence		
2.	Nitrogen Dioxide (NO <sub>2</sub> ), µg/m <sup>3</sup>	Annual *	40	30	- Modified Jacob & Hochheiser ( Na-Arsenite)		
<u>.</u>		24 Hours **	80	80	- Chemiluminescence		
3.	Particulate Matter (size less than 10µm) or	Annual *	60	60	-Gravimetric - TOEM		
	$PM_{10}\mu g/m^3$	24 Hours **	100	100	- Beta Attenuation		
4.	Particulate Matter (size less than 2.5µm) or	Annual *	40	40	-Gravimetric - TOEM		
	$PM_{2.5} \mu g/m^3$	24 Hours **	60	60	- Beta Attenuation		
5.	Ozone (O <sub>3</sub> ) µg/m <sup>3</sup>	8 Hours **	100	100	- UV Photometric - Chemiluminescence		
		1 Hours **	180	180	- Chemical Method		
6.	Lead (Pb) µg/m³	Annual *	0.50	0.50	-AAS/ICP method after sampling on EMP 2000 or equivalent filter		
		24 Hours **	1.0	1.0	paper ED-XRF using Teflon filter		
7.	Carbon Monoxide (C()) mg/m³	8 Hours **	02	02	- Non Dispersive Infra Red (NDIR) Spectroscopy		
		1 Hours **	04	04			
8.	Ammonia (NH <sub>3</sub> ) μg/m <sup>3</sup>	Annual*	100	100	-Chemiluminescence - Indophenol Blue Method		
		24 Hours**	400	400			
9.	Benzene (C <sub>6</sub> H <sub>6</sub> ) μg/m <sup>3</sup>	Annul *	05	05	-Gas Chromatography based continuous analyzer - Adsorption and Desorption followed by GC analysis		
10.	Benzo (a) Pyrene (BaP)- Particulate phase only, ng/m <sup>3</sup>	Annual*	01	01	-Solvent extraction followed by HPLC/GC analysis		
11.	Arsenic (As), ng/m <sup>3</sup>	Annual*	06	06	-AAS/ICP method after sampling on EPM 2000 or equivalent filter paper		
12.	Nickel (Ni),ng/m³	Annual*	20	20	-AAS/ICP method after sampling on EPM 2000 or equivalent filter paper		

<sup>\*\*</sup> Annual arithmetic mean of minimum I04 measurements in a year at a particular site taken twice a week 24 hourly at uniform intervals.

<sup>\*\* 24</sup> hourly or 08 hourly or 0I hourly monitored values, as applicable, shall be complied with 98% of the time in a year, 2% of the time, they may exceed the limits but not on two consecutive days of monitoring.