



BY REGD. POST WITH AD

STATE POLLUTION CONTROL BOARD, ODISHA

A/118, Nilakantha Nagar, Unit-VIII, Bhubaneswar-751012 Phone-2561909, Fax: 2562822, 2560955

CONSENT ORDER

No. 5/22 /IND-I-CON-207 Dt. 26.03.2021/

CONSENT ORDER NO.190

Sub: Consent for discharge of sewage and trade effluent under section 25/26 of Water (PCP) Act, 1974 and for existing / new operation of the plant under section 21 of Air (PCP) Act, 1981.

Ref: Your online application No. 2873360, Dated 31-12-2020 and online reply dated 21.01.2021.

Consent to operate is hereby granted under section 25/26 of Water (Prevention & Control of Pollution) Act, 1974 and under section 21 of Air (Prevention & Control of Pollution) Act, 1981 and rules framed thereunder to

Name of the Industry: HIRAKHAND BUNDIA UNDER GROUND MINE OF M/S. MCL

Name of the Occupier & Designation: PRIYA SHANKAR SINHA, SUB-AREA MANAGER,

HIRAKHAND BUNDIA UG MINE

Address:

RAMPUR SUB-AREA, AT/PO: RAMPUR COLLIERY,

DIST: JHARSUGUDA, PIN-768225

This consent order is valid for the period up to 31.03.2022 from the date of issue of

this order.

This consent order supersedes the earlier consent order issued vide letter No. 3753 dated 21.03.2020. This consent to operate is granted in view of orders of the Hon'ble Supreme Court dated 08.05.2013 in the writ petition (Civil) No. (S) 202 of 1995 and also subject to the final outcome of the Hon'ble Supreme Court order.

Details of Products Manufactured

SI. No. Pr	Product	Quantity
1.	Coal	0.95 MTPA

This consent order is valid for the specified outlets, discharge quantity and quality, specified chimney/stack, emission quantity and quality of emissions as specified below. This consent is granted subject to the general and special conditions stipulated therein.

Discharge permitted through the following outlet subject to the standard

	- intian of	Point of	ription of Point of Quantity Pre-scribe					
Out let No.	outlet	discharge	of discharge KL/hr	рН	TSS (mg/l)	Oil & Grease (mg/l)	BOD (mg/l)	COD (mg/l)
01	Outlet of Septic tank (Domestic effluent)	Soak pit		5.5-9.0	200		100	
02	Mine strata water / surface run off / other wastewater	On land / inland surface water body	95.75 (Max.)	5.5 to 9.0	100	10		250

Emission permitted through the following stack subject to the prescribed B.

tandard Chimney Stack No.	Description of Stack	Stack height (m)	Quantity of emission	Prescribed Standard			
				PM (mg/Nm³)	SO ₂	NOx	
						-	

Disposal of solid waste permitted in the following manner C.

SI.	Type of Solid waste	Quantity generated (TPD)	Quantity to	Quantity	disposed	Description of disposal site.



D. GENERAL CONDITIONS FOR ALL UNITS

- 1. The consent is given by the Board in consideration of the particulars given in the application. Any change or alternation or deviation made in actual practice from the particulars furnished in the application will also be the ground liable for review/variation/revocation of the consent order under section 27 of the Act of Water (Prevention & Control of Pollution) Act, 1974 and section 21 of Air (Prevention & Control of Pollution) Act, 1981 and to make such variations as deemed fit for the purpose of the Acts.
- The industry would immediately submit revised application for consent to operate to this Board in the event of any change in the quantity
 and quality of raw material / and products / manufacturing process or quantity /quality of the effluent rate of emission / air pollution control
 equipment / system etc.
- The applicant shall not change or alter either the quality or quantity or the rate of discharge or temperature or the route of discharge without the previous written permission of the Board.
- 4. The application shall comply with and carry out the directives/orders issued by the Board in this consent order and at all subsequent times without any negligence on his part. . In case of non-compliance of any order/directives issued at any time and/or violation of the terms and conditions of this consent order, the applicant shall be liable for legal action as per the provisions of the Law/Act.
- 5. The applicant shall make an application for grant of fresh consent at least 90 days before the date of expiry of this consent order.
- 6. The issuance of this consent does not convey any property right in either real or personal property or any exclusive privileges nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of Central, State laws or regulation.
- This consent does not authorize or approve the construction of any physical structure or facilities or the undertaking of any work in any natural water course.
- 8. The applicant shall display this consent granted to him in a prominent place for perusal of the public and inspecting officers of this Board.
- 9. An inspection book shall be opened and made available to Board's Officers during the visit to the factory.
- 10. The applicant shall furnish to the visiting officer of the Board any information regarding the construction, installation or operation of the plant or of effluent treatment system / air pollution control system / stack monitoring system any other particulars as may be pertinent to preventing and controlling pollution of Water / Air.
- 11. Meters must be affixed at the entrance of the water supply connection so that such meters are easily accessible for inspection and maintenance and for other purposes of the Act provided that the place where it is affixed shall in no case be at a point before which water has been taped by the consumer for utilization for any purposes whatsoever.
- 12. Separate meters with necessary pipe-line for assessing the quantity of water used for each of the purposes mentioned below:
 - a) Industrial cooling, spraying in mine pits or boiler feed,
 - b) Domestic purpose
 - c) Process
- 13. The applicant shall display suitable caution board at the lace where the effluent is entering into any water-body or any other place to be indicated by the Board, indicating therein that the area into which the effluents are being discharged is not fit for the domestic use/bathing.
- 14. Storm water shall not be allowed to mix with the trade and/or domestic effluent on the upstream of the terminal manholes where the flow measuring devices will be installed.
- 15. The applicant shall maintain good house-keeping both within the factory and the premises. All pipes, valves, sewers and drains shall be leak-proof. Floor washing shall be admitted into the effluent collection system only and shall not be allowed to find their way in storm drains or open areas.
- 16. The applicant shall at all times maintain in good working order and operate as efficiently as possible all treatment or control facilities or systems install or used by him to achieve with the term(s) and conditions of the consent.
- 17. Care should be taken to keep the anaerobic lagoons, if any, biologically active and not utilized as mere stagnation ponds. The anaerobic lagoons should be fed with the required nutrients for effective digestion. Lagoons should be constructed with sides and bottom made impervious.
- 18. The utilization of treated effluent on factory's own land, if any, should be completed and there should be no possibility of the effluent gaining access into any drainage channel or other water courses either directly or by overflow.
- 19. The effluent disposal on land, if any, should be done without creating any nuisance to the surroundings or inundation of the lands at any time.
- 20. If at any time the disposal of treated effluent on land becomes incomplete or unsatisfactory or create any problem or becomes a matter of dispute, the industry must adopt alternate satisfactory treatment and disposal measures.
- 21. The sludge from treatment units shall be dried in sludge drying beds and the drained liquid shall be taken to equalization tank.
- 22. The effluent treatment units and disposal measures shall become operative at the time of commencement of production.
- 23. The applicant shall provide port holes for sampling the emissions and access electrical outlet points and other arrangements for chimneys/stacks and other sources of emissions so as of collect samples of emission by the Board or the applicant at any time in accordance with the provision of the Act or Rules made therein.

ODISHA

CONSENT ORDER HIRAKHAND BUNDIA UG MINE OF M/S. MCL

- The applicant shall provide all facilities and render required assistance to the Board staff for collection of samples / stack monitoring /
- Inspection.

 The applicant shall not change or alter either the quality or quantity or rate of emission or install, replace or alter the air pollution control equipment or change the raw material or manufacturing process resulting in any change in quality and/or quantity of emissions, without 24. 25. the previous written permission of the Board.
- No control equipments or chimney shall be altered or replaced or as the case may be erected or re-erected except with the previous 26. approval of the Board.
- The liquid effluent arising out of the operation of the air pollution control equipment shall be treated in the manner and to ion of standards prescribed by the Board in accordance with the provisions of Water (Prevention and Control of Pollution) Act, 1974 (as amended). 27.
- The stack monitoring system employed by the applicant shall be opened for inspection to this Board at any time. 28.
- There shall not be any fugitive or episodal discharge from the premises.
- In case of such episodal discharge/emissions the industry shall take immediate action to bring down the emission within the limits 29. prescribed by the Board in conditions/stop the operation of the plant. Report of such accidental discharge /emission shall be brought to the 30. notice of the Board within 24 hours of occurrence.
- The applicant shall keep the premises of the industrial plant and air pollution control equipments clean and make all hoods, pipes, valves, stacks/chimneys leak proof. The air pollution control equipments, location, inspection chambers, sampling port holes shall be made easily
- Any upset condition in any of the plant/plants of the factory which is likely to result in increased effluent discharge/emission of air pollutants and / or result in violation of the standards mentioned above shall be reported to the Headquarters and Regional Office of the Board by fax / 32.
- The industry has to ensure that minimum three varieties of trees are planted at the density of not less than 1000 trees per acre. The trees may be planted along boundaries of the industries or industrial premises. This plantation is stipulated over and above the bulk plantation of 33.
- The solid waste such as sweeping, wastage packages, empty containers residues, sludge including that from air pollution control equipments collected within the premises of the industrial plants shall be disposed off scientifically to the satisfaction of the Board, so as no 34. to cause fugitive emission, dust problems through leaching etc., of any kind.
- All solid wastes arising in the premises shall be properly classified and disposed off to the satisfaction of the Board by : 35.
 - Land fill in case of inert material, care being taken to ensure that the material does not give rise to leachate which may percolate into ground water or carried away with storm run-off.
 - Controlled incineration, wherever possible in case of combustible organic material.
 - Composting, in case of bio-degradable material.
- Any toxic material shall be detoxicated if possible, otherwise be sealed in steel drums and buried in protected areas after obtaining approval of this Board in writing. The detoxication or sealing and burying shall be carried out in the presence of Board's authorized persons only. 36 Letter of authorization shall be obtained for handling and disposal of hazardous wastes.
- If due to any technological improvement or otherwise this Board is of opinion that all or any of the conditions referred to above requires variation (including the change of any control equipment either in whole or in part) this Board shall after giving the applicant an opportunity of being heard, vary all or any of such condition and thereupon the applicant shall be bound to comply with the conditions so varied. 37.
- The applicant, his/heirs/legal representatives or assignees shall have no claim whatsoever to the condition or renewal of this consent after 38. the expiry period of this consent.
- The Board reserves the right to review, impose additional conditions or condition, revoke change or alter the terms and conditions of this 39
- Notwithstanding anything contained in this conditional letter of consent, the Board hereby reserves to it the right and power under section 27(2) of the Water (Prevention & Control of Pollution) Act, 1974 to review any and/or all the conditions imposed herein above and to make such variations as deemed fit for the purpose of the Act by the Board.
- The conditions imposed as above shall continue to be in force until revoked under section 27(2) of the Water (Prevention & Control of Pollution) Act, 1974 and section 21 A of Air (Prevention & Control of Pollution) Act, 1981. 41.
- In case the consent fee is revised upward during this period, the industry shall pay the differential fees to the Board (for the remaining years) to keep the consent order in force. If they fail to pay the amount within the period stipulated by the Board the consent order will be revoked without prior notice.
- The Board reserves the right to revoke/refuse consent to operate at any time during period for which consent is granted in case any violation is observed and to modify/ stipulate additional conditions as deemed appropriate 43.

GENERAL CONDITIONS FOR UNITS WITH INVESTMENT OF MORE THAN Rs 50 CRORES, AND 17 CATEGORIES OF HIGHLY POLLUTING INDUSTRIES (RED A).

- The applicant shall analyse the emissions every month for the parameters indicated in TABLE .B & C as mentioned in this order and shall furnish the report thereof to the Board by the 10th of the succeeding month. 1.
- The applicant shall provide and maintain at his own cost three ambient air quality monitoring stations for monitoring Suspended Particulate Matter, Sulphor Dioxide, Oxides of Nitrogen, Hydro-Carbon, Carbon-Monixide and monitor the same once in a day/week/fortnight/month. The data collected shall be maintained in a register and a monthly extract be furnished to the Board. 2.



- The applicant shall provide and maintain at his own cost a meteorological station to collect the data on wind velocity, direction, temperature, humidity, rainfall, etc. and the daily reading shall be recorded and the extract sent to the Board once in a month.
- The applicant shall forward the following information to the Member Secretary, State Pollution Control Board, Odisha, Bhubaneswar regularly.
 - a. Report of analysis of stack monitoring, ambient air quality monitoring meteorological data as required every month.
 - b. Progress on planting of trees quarterly.
- The applicant shall install mechanical composite sampling equipment and continuous flow measuring / recording devices on the effluent drains of trade as well as domestic effluent. A record of daily discharge shall be maintained.
- The following information shall be forwarded to the Member Secretary on or before 10th of every month.
 - Performance / progress of the treatment plant.
 - b. Monthly statement of daily discharge of domestic and/or trade effluent.

7. Non-compliance with effluent limitations

- If for any reason the applicant does not comply with or is unable to comply with any effluent limitations specified in this consent, the applicant shall immediately notify the consent issuing authority by telephone and provide the consent issuing authority with the following information in writing within 5 days of such notification.
 - i) Causes of non-compliance
 - i) A description of the non-compliance discharge including its impact on the receiving waters.
 - ii) Anticipated time of continuance of non-compliance if expected to continue or if such condition has been corrected the duration or period of non-compliance.

南

- iii) Steps taken by the applicant to reduce and eliminate the non-complying discharge and
- iv) Steps to be taken by the applicant too prevent the condition of non-compliance.
- b) The applicant shall take all reasonable steps to minimize any adverse impact to natural waters resulting from non-compliance with any effluent limitation specified in this consent including such accelerated or additional monitoring as necessary to determine the nature and impact of the non-complying discharge.
- c) Nothing in this consent shall be construed to relieve the applicant from civil or criminal penalties for non-compliance whether or not such non-compliance is due to factors beyond his control, such as break-down, electric failure, accident or natural disaster.
- 8. The applicant shall at his own cost get the effluent samples collected both before and after treatment and get them analysed at an approval laboratory every month for the parameters indicated in Part-D and shall submit in duplicate the report thereof to the Board.
- The addition of various treatment chemicals should be done only with mechanical dosers and proper equipment for regulation of correct dosages determined daily and for proper uniform feeding. Crude practices such as dumping of chemicals in drains or sumps or trickling of acids or alkalies arbitrarily and utilizing poles for stirring etc. should not be resorted to.
- 10. In the disposal of treated effluent on land for irrigation, the industry shall keep in view of the need for;
 - Rotation of crops
 - Change of point of application of effluent on land
 - A portion of land kept fallow.
- 11. The adoption of these would avoid soil becoming sick or slate, the industry may ensure this in consultation with the Agriculture Department.
- 12. It is the sole responsibility of the industry to ensure that there are no complaints at any time from the royats in the surrounding areas as a result of discharge of sewage or trade effluent if any.
- 13. Proper house keeping shall be maintained by a dedicated team.
- 14. The industry must constitute a team of responsible and technically qualified personnel who will ensure continuous operation of all pollution control devices round the clock (including night hours) and should be in a position to explain the status of operation of the pollution control measures to the inspecting officers of the Board at any point of time. The name of these persons with their contact telephone numbers shall be intimated to the concerned. Regional Officer and Head Office of the Board and in case of any change in the team it shall be intimated to the Board immediately.

ODISHA (

CONSENT ORDER HIRAKHAND BUNDIA UG MINE OF M/S, MCL

E. SPECIAL CONDITIONS:

- Mining operation is subject to availability of all other statutory clearances.
- The mine strata water shall be adequately treated and shall remain within the prescribed standards. Effort shall be made to use the mine strata water for various mining activities instead of discharging to outside.
- The strata water and surface runoff of the mine shall be routed through the existing storage-cum-settling pond. Under no circumstances it shall be discharged bypassing the storage-cum-settling pond.
- Domestic effluents shall be discharged to soak pit via septic tank constructed as BIS specification.
- 5. Regular monitoring of ground water level and quality should be carried out by establishing a network of existing wells. The monitoring should be done four times a year in pre-monsoon (April/May), monsoon (August), post-monsoon (November) and winter (January) seasons. Data thus collected should be submitted to the Board quarterly.
- Garland drain terminating with a settling pond of adequate capacity shall be constructed for storage and reuse of surface runoff generated during monsoon from the coal stockyard. This shall be done by 31.5.2021.
- Dust suppression measures through fixed water sprinkling system with rain guns shall be provided at coal stack yard and other coal handling areas. This shall be done by 31.7.2021.
- Regular water spraying shall be done on haulage road and other potential dust generation areas to suppress fugitive dust.
- The haulage roads shall be maintained properly as soon as any ruts and potholes develop in the road.
- Steps shall be taken for blacktopping of major approach road and haulage roads and other coal transportation roads.
- Necessary precautionary measures shall be taken for maintaining a minimum stock to avoid fire hazards in the coal stack yard.



- 12. Ambient air quality and noise quality monitoring shall be carried out at appropriate places (at three appropriate locations within the lease area) of the mine and it shall comply the following standards.
 - (a) Ambient air quality measured at a distance of 500m from the dust generating sources in the down wind direction shall meet the following standards.

Pollutant Concentration in (microgram/m³) (24 hourly)

SPM	~	500
RPM (Size less than 10μm)	-	250
SO ₂	-	120
NO _x	-	120

In case any residential or commercial or industrial place falls within 500 metres of any generating sources, the National Ambient Air Quality Standards for industrial area notified shall be applicable.

(b)	Noise level-	6 AM- 10 PM	+	75 dB(A)
		10 PM-6 AM	_	70 dB(A)

The location of monitoring station shall be fixed in consultation with Regional Officer, SPC Board, Jharsuguda.

- 13. Monitoring of Ambient Air Quality of the mine shall be done once in a fortnight (24 hourly) and the consolidated data shall be submitted to the State Pollution Control Board once in a year.
- 14. Any solid waste if so generated during the mining operation shall be utilized for filling the voids created in the mine itself as per the approved mining plan.
- 15. Green belt and plantation of indigenous species shall be done in available vacant land. The plantation details along with the survival percentage shall be submitted in the environment statement report every year.
- 16. The mine shall take appropriate action for providing drinking water in the peripheral villages.
- 17. Ambient air quality monitoring data, noise monitoring data and water / wastewater quality monitoring data shall be electronically displayed at the entry point of the mine or at a suitable location of the mine.

- The annual coal production and compliance status report of the stipulated conditions shall be submitted to the Board latest by 30th April every year. 18.
- The environmental statement report for the financial year ending 31st March shall be submitted to the Board in form -V on or before 30th September every year. 19.

MEMBER SECRETARY STATE POLLUTION CONTROL BOARD, ODISHA

To,

THE SUB AREA MANAGER, HIRAKHAND BUNDIA UNDER GROUND MINE, M/S. MCL, RAMPUR SUB-AREA, AT/PO: RAMPUR COLLIERY,

DIST: JHARSUGUDA, PIN - 768 225

	/Dt	
Memo No	/Dt	
a samuardad to		

Copy forwarded to:

- Regional Officer, State Pollution Control Board, Jharsuguda. i)
- District Collector Jharsuguda ii)
- Director of Mines, Govt. of Odisha, Bhubaneswar
- Director, Environment-cum-Special Secretary, F & E. Deptt. Govt. of Odisha, (iii iv) Bhubaneswar.
- D.F.O Sambalpur V)
- Deputy Director of Mines, Sambalpur vi)
- Chief Env. Engineer (Hazardous waste management cell) vii)
- Chief Env. Scientist, Central Lab. SPCB, Bhubaneswar viii)
- Consent Register ix)

CHIEF ENV. ENGINEER (M) STATE POLLUTION CONTROL BOARD, ODISHA

GENERAL STANDARDS FOR DISCHARGE OF ENVIRONMENT POLLUTANTS



GENERAL STANDARDS FOR DISCHARGE OF ENVIRONMENTAL POLLUTANTS PART -A: EFFLUENTS

	Deremeters		S	tandards			
I.No.	Parameters	Inland surface	Public sewers	Land for irrigation	Marine Costal Areas		
		(2)	(b)	(c)	(d)		
•	Colour & odour Colourless/Odrless as far as practible		ourless/Odou See 6 of Annex-1		less/Odou See 6 of Annex-1 See 6 of A		See 6 of Annex-1
. Suspended Solids (mg/l)		100	600	200	For process wastewater – 100 b. For cooling water effluent 10% above total suspended matter of influent.		
3.	Particular size of SS	Shall pass 850					
5.	pH value	5.5 to 9.0	5.5 to 9.0	5.5 to 9.0	5.5 to 9.0		
6.	Temperature	Shall not exceed 5°C above the receiving water temperature			Shall not exceed 5°C above the receiving water temperature		
7.	Oil & Grease mg/l max.	10	20	10	20		
	Total residual chlorine	1.0			1.0		
8. 9.	Ammonical nitrogen (as	50	50		50		
10.	N) mg/l max. Total Kajeldahl nitroge	100			100		
10.	(as NH ₃) mg/1 max.				5.0		
11.	Free ammonia (as NH mg/1 max.	5.0			100		
12.	Biochemical Oxygen Demand (5 days at (20°C) mg/1 max.	30	350	100	250		
13.	100	250			0.0		
14.	1 (1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	0.2	0.2	0.2			
15	. Mercury (as Hg) mg/	1 0.01	0.01		=		
16	max. Lead (as pb) mg/1 m	ax. 01.	1.0		2.0		



17.	Cardmium (as Cd) mg/1 max.	2.0	1.0		2.0
18.	Hexavalent Chromium (as Cr + 6) mg/l max.	0.1	2.0		1.0
19.	Total Chromium (as Cr) mg/l max.	2.0	2.0		2.0
20.	Copper (as Cu) mg/l max.	3.0	3.0		3.0
21.	Zinc (as Zn) mg/l max.	5.0	15		15
22.	Selenium (as Sc) mg/l max.	0.05	0.05		0.05
23.	Nickel (as Nil) mg/l max.	3.0	3.0		5.0
24.	Cyanide (as CN) mg/l max.	0.2	2.0	0.2	0.02
25.	Fluoride (as F) mg/l max.	2.0	15		15
26.	Dissolved Phosphates (as P) mg/l max.	5.0			
27.	Sulphide (as S) mg/l max.	2.0			5.0
28.	Phennolic compounds as (C ₆ H ₅ OH) mg/l max.	1.0	5.0		5.0
29.	Radioactive materials a. Alpha emitter micro curle/ml. b. Beta emitter micro curle/ml.	10 ⁷	10 ⁷	10 ⁸	10 ⁷
30.	Bio-assay test	90% survival of fish after 96 hours in 100% effluent	90% survival of fish after 96 hours in 100% effluent	90% survival of fish after 96 hours in 100% effluent	90% survival of fish after 96 hours in 100% effluent
31	Manganese (as Mn)	2 mg/l	2 mg/l		2 mg/l
32.	Iron (Fe)	3 mg/l	3 mg/l		3 mg/l
33.	Vanadium (as V)	0.2 mg/l	0.2 mg/l		0.2 mg/l
34.	Nitrate Nitrogen	10 mg/l			20 mg/l



NATIONAL AMBIENT AIR QUALITY STANDARDS

		Time Weighed		Concentrate of	
l. Io.		Average	Industrial Residential, Rural and other Area	Ecologically Sensitive Area (notified by Central Government)	Methods of Measurement
			(4)	(5)	(6)
(1)	(2)	(3)	(4)	20	-Improved west and Gaeke
1.	Sulphur Dioxide (SO ₂),	Annual *	50		
	μg/m³	24 Hours **	80	80	- Ultraviolet fluorescence - Modified Jacob & Hochheiser (
		Annual *	40	30	Na-Arsenite)
2.	Nitrogen Dioxide	Annual			- Chemiluminescence
	(NO ₂), $\mu g/m^3$	24 Hours **	80	80	-Gravimetric
	Particulate Matter (size	Annual *	60	60	- TOEM
3.	less than 10µm) or		100	100	- Beta Attenuation
	PM ₁₀ µg/m ³	24 Hours **	100	40	-Gravimetric
4.	Particulate Matter (size	Annual *	40	40	- TOEM
4.	less than 2.5µm) or	ativity.	60	60	- Beta Attenuation
	$PM_{2.5} \mu g/m^3$	24 Hours **		100	- UV Photometric
5.	Ozone (O ₃) µg/m ³	8 Hours **	100	100	- Chemiluminescence
J.	Ozone (S) Po		180	180	- Chemical Method
		1 Hours ** Annual *	0.50	0.50	-AAS/ICP method after sampling on EMP 2000 or equivalent filter
6.	Lead (Pb) μg/m ³	Annual			paper.
		24 Hours **	Hours ** 1.0	1.0	ED VPE using Teflon filter
				02	- Non Dispersive Infra Red (NDIR)
7	Carbon Monoxide	8 Hours **	02	02	Spectroscopy
7.	(CO) mg/m ³		04	04	
		1 Hours **	100	100	-Chemiluminescence
8.	Ammonia (NH ₃) μg/m	3 Annual*	100		- Indophenol Blue Method
		24 Hours**	400	400	-Gas Chromatography based
	12.77	1 +	05	05	continuous analyzer
9.	Benzene (C ₆ H ₆) μg/m ³	71111111			- Adsorption and Desorption
					followed by GC analysis
			- 01	01	-Solvent extraction followed by
10	. Benzo (a) Pyrene (BaP))- Annual*	01		HPLC/GC analysis
1.0	Particulate phase only,				to (XCD) and ofter compline
	ng/m³	Annual*	06	06	-AAS/ICP method after sampling on EPM 2000 or equivalent filter
11	Arsenic (As), ng/m ³	Annual			
		_			-AAS/ICP method after sampling
-	2. Nickel (Ni),ng/m ³	Annual*	20	20	on EPM 2000 or equivalent filter
13	Z. Nickel (111),118/111				paper particular site taken twice a week 24

^{**} Annual arithmetic mean of minimum I04 measurements in a year at a particular site taken twice a week 24 hourly at uniform intervals.

^{** 24} hourly or 08 hourly or 0I hourly monitored values, as applicable, shall be complied with 98% of the time in a year, 2% of the time, they may exceed the limits but not on two consecutive days of monitoring.