

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687788555391

अनुबंध तिथि | Generated Date : 01-Mar-2024

बोली/आरए/पीबीपी संख्या | Bid/RA/PBP No.: [GEM/2023/B/3927289](#)

अनुसूची नाम | Schedule Name: Schedule 4, Schedule 3, Schedule 6, Schedule 2, Schedule 1

संगठन विवरण Organisation Details	खरीदार विवरण Buyer Details
प्ररूप Type : Central PSU मंत्रालय Ministry : Ministry of Coal विभाग Department : MAHANADI COALFIELDS LIMITED संगठन का नाम Organisation Name : MAHANADI COALFIELDS LIMITED कार्यालय क्षेत्र Office Zone : MAHANADI COALFIELDS LIMITED	पद Designation : Sunil Dajgude Dy Mgr MM संपर्क नंबर Contact No. : - ईमेल आईडी Email ID : sunilt.dajgude@coalindia.in जीएसटीआईएन GSTIN : 21AABCM5188P1Z3 पता Address : MAHANADI COALFIELDS LIMITED, PO - JAGRUTI VIHAR, BURLA, SAMBALPUR, ODISHA-768020, India

वित्तीय स्वीकृति विवरण Financial Approval Detail	भुगतान प्राधिकरण विवरण Paying Authority Details
आईएफडी सहमति IFD Concurrence : No प्रशासनिक अनुमोदन का पदनाम Designation of Administrative Approval: GM(MM)/HOD वित्तीय अनुमोदन का पदनाम Designation of Financial Approval: DY GM(FIN)	भुगतान का तरीका Role: PAO भुगतान का तरीका Payment Mode: Internet Banking पद Designation : DEEPAK KUMAR BURMA MGR FIN ईमेल आईडी Email ID : dkburma@coalindia.in जीएसटीआईएन GSTIN : 21AABCM5188P1Z3 पता Address: MAHANADI COALFIELDS LIMITED, AT /PO - JAGRUTI VIHAR, BURLA, SAMBALPUR, ODISHA-768020, India

विक्रेता विवरण Seller Details	
जेम विक्रेता आईडी GeM Seller ID :	0F03180000106096
कंपनी का नाम Company Name :	shree bhagwati cables
संपर्क नंबर Contact No. :	09818559780
ईमेल आईडी Email ID :	SBCCABLES@GMAIL.COM
पता Address :	C-426, C 426, DSIIIC INDUSTRIAL AREA, NARELA, DELHI, NORTH WEST DELHI, DELHI-110040, -
एमएसएमई पंजीकरण संख्या MSME Registration number :	UDYAM-DL-10-0006773
एमएसई सामाजिक श्रेणी MSE Social Category :	General
एमएसई लिंग श्रेणी MSE Gender :	Male
जीएसटीआईएन GSTIN:	07AANFS1701R1ZQ

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 95 sq mm ब्रांड Brand : SBC ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue कैसे बेचा जा रहा है Selling As : OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor as per IS 1554 (Part 1) (Q3) मॉडल Model: 95 SQMM 4 CORE ALU ARMD (MAKE SBC) एचएसएन कोड HSN Code: 85446090	2,250	meter	378	NA	850,500
2	उत्पाद का नाम Product Name : SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 70 sq mm ब्रांड Brand : SBC ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue कैसे बेचा जा रहा है Selling As : OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor as per IS 1554 (Part 1) (Q3) मॉडल Model: 70 SQMM 4 CORE ALU ARMD (MAKE-SBC)	9,000	meter	281	NA	2,529,000

	एचएसएन कोड HSN Code: 8544					
3	<p>उत्पाद का नाम Product Name : SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 240 sq mm</p> <p>ब्रांड Brand : SBC</p> <p>ब्रांड प्रकार Brand Type : Registered Brand</p> <p>कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue</p> <p>कैसे बेचा जा रहा है Selling As : OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor as per IS 1554 (Part 1) (Q3)</p> <p>मॉडल Model: 240 SQMM 4 CORE ALU ARMD (MAKE-SBC)</p> <p>एचएसएन कोड HSN Code: 85446090</p>	7,800	meter	863	NA	6,731,400
4	<p>उत्पाद का नाम Product Name : SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 50 sq mm</p> <p>ब्रांड Brand : SBC</p> <p>ब्रांड प्रकार Brand Type : Registered Brand</p> <p>कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue</p> <p>कैसे बेचा जा रहा है Selling As : OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor as per IS 1554 (Part 1) (Q3)</p> <p>मॉडल Model: 50 SQMM 4 CORE ALU ARMD (MAKE-SBC)</p> <p>एचएसएन कोड HSN Code: 85446090</p>	4,250	meter	215	NA	913,750
5	<p>उत्पाद का नाम Product Name : SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 35 sq mm</p> <p>ब्रांड Brand : SBC</p> <p>ब्रांड प्रकार Brand Type : Registered Brand</p> <p>कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue</p> <p>कैसे बेचा जा रहा है Selling As : OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor as per IS 1554 (Part 1) (Q3)</p> <p>मॉडल Model: 35 SQMM 4 CORE ALU ARMD (MAKE-SBC)</p> <p>एचएसएन कोड HSN Code: 8544</p>	11,000	meter	161.2	NA	1,773,200
कुल ऑर्डर मूल्य Total Order Value (in INR)						12,797,850

परोषिती विवरण | Consignee Detail

क्र.सं. S.No	परोषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	<p>पद Designation :- ईमेल आईडी Email ID : depot-off-basa.mcl@coalindia.in संपर्क Contact : 87890-15874- जीएसटीआईएन GSTIN : 21AABCM5188P1Z3 पता Address : Mahanadi Coalfields Limited, At & Po- Basundhara, Sundargarh, Basundhara-770076, SUNDERGARH, ODISHA-770076, India</p>	SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 95 sq mm	-	250	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 70 sq mm	-	700	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 240 sq mm	-	400	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 50	-	1,000	01-Mar-2024	29-Jun-2024

		sq mm				
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 35 sq mm	-	2,500	01-Mar-2024	29-Jun-2024
2	<p>पद Designation :- ईमेल आईडी Email ID : doredlatharun.sai@coalindia.in संपर्क Contact :- जीएसटीआईएन GSTIN :- पता Address : MAHANADI COALFIELDS LIMITED, AT & PO - JAGRUTI VIHAR, BURLA, SAMBALPUR, ODISHA-768020, India</p>	SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 70 sq mm	-	1,500	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 240 sq mm	-	2,000	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 35 sq mm	-	2,400	01-Mar-2024	29-Jun-2024
3	<p>पद Designation :- ईमेल आईडी Email ID : depot-off-jaga.mcl@nic.in संपर्क Contact : 94388-77340- जीएसटीआईएन GSTIN : 21AABCM5188P1Z3 पता Address : Office of the Depot Officer, Central/Regional Stores, Jagannath /Area, P.O. Balanda, ANGUL, ODISHA-759116, India</p>	SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 95 sq mm	-	1,100	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 70 sq mm	-	4,400	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 240 sq mm	-	4,200	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 50 sq mm	-	1,500	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 35 sq mm	-	4,700	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy				

4	<p>पद Designation :- ईमेल आईडी Email ID : depot-off-lkpa.mcl@coalindia.in संपर्क Contact : 094-38493852- जीएसटीआईएन GSTIN : 21AABCM5188P1Z3 पता Address : Office of the Chief General Manager, Mahanadi Coalfields Limited, Lakhanpur Area, At/PO Bandhbahal, Via, Belpahar, JHARSUGUDA, ODISHA-768211, India</p>	Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 95 sq mm	-	900	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 70 sq mm	-	2,400	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 240 sq mm	-	1,200	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 50 sq mm	-	1,750	01-Mar-2024	29-Jun-2024
		SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 35 sq mm	-	1,400	01-Mar-2024	29-Jun-2024

Product Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 95 sq mm

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
GENERIC	Conformity of the specification	as per IS:1554 (Part 1):1988 latest
	BIS Marked	Yes for Type-A Insulation, Yes for Type-C Insulation
	BIS License Number (CM/L Number) - Must declare	2600640
	No. of core	4
	Nominal Area of Conductor (in Sq.mm)	95
CONSTRUCTION	Conductor material (Complying with IS:8130:1984 latest)	Aluminium
	Construction of Conductor	Stranded
	Type of Insulation	General purpose
	Type of PVC compound for insulation	Type - A
	Type of PVC compound for outer sheath	Type ST-1
	Filler and inner sheath	Thermoplastic materials
	Armouring	Galvanized steel strip armoured
	Improved fire performance category	1
MARKING	Identification on the cable	as per Cl. 17 of IS:1554 (Part 1) latest
	Packing and marking	as per Cl. 18 of IS:1554 (Part 1) latest
OPTIONAL TEST REPORTS	Availability of test reports for Cold bend test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Cold impact test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Armour resistance test (If reports available select 1, If reports not available select 0)	1

CERTIFICATIONS	Availability of Type test report with improved fire performance from Central government/NABL/ILAC accredited laboratory to prove the conformity of the specification	Yes with optional test reports
	Test report number - Must declare	internal report
	Report date - Must declare	internal report
	Name of lab - Must declare	internal report
	Address of lab - Must declare	internal report
	Agreed to furnish all the test reports and certification to buyer / consignee on demand	Yes

खरीदार परिभाषित अतिरिक्त विशिष्टता के लिए | Buyer Defined Additional Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 95 sq mm

विनिर्देश Specification	मूल्य Value
Identification on the cable as per Cl. 17 of IS:1554 (Part 1) latest Packing and marking as per Cl. 18 of IS:1554 (Part 1) latest	Agree
Conductor material (Complying with IS:8130:1984 latest)	Aluminium
Conformity of the specification as per IS:1554 (Part 1):1988 latest	Agree
Standard cable length on a drum	250 meter (+/- 5%)

Product Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 70 sq mm

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
GENERIC	Conformity of the specification	as per IS:1554 (Part 1):1988 latest
	BIS Marked	Yes for Type-A Insulation, Yes for Type-C Insulation
	BIS License Number (CM/L Number) - Must declare	8579810
	No. of core	4
	Nominal Area of Conductor (in Sq.mm)	70
CONSTRUCTION	Conductor material (Complying with IS:8130:1984 latest)	Aluminium
	Construction of Conductor	Stranded
	Type of Insulation	General purpose
	Type of PVC compound for insulation	Type - A
	Type of PVC compound for outer sheath	Type ST-1
	Filler and inner sheath	Thermoplastic materials
	Armouring	Galvanized steel strip armoured
	Improved fire performance category	1
MARKING	Identification on the cable	as per Cl. 17 of IS:1554 (Part 1) latest
	Packing and marking	as per Cl. 18 of IS:1554 (Part 1) latest
OPTIONAL TEST REPORTS	Availability of test reports for Cold bend test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Cold impact test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Armour resistance test (If reports available select 1, If reports not available select 0)	1
CERTIFICATIONS	Availability of Type test report with improved fire performance from Central government/NABL/ILAC accredited laboratory to prove the conformity of the specification	Yes with optional test reports
	Test report number - Must declare	INTERNAL REPORT
	Report date - Must declare	INTERNAL REPORT
	Name of lab - Must declare	INTERNAL REPORT
	Address of lab - Must declare	INTERNAL REPORT
	Agreed to furnish all the test reports and certification to buyer / consignee on demand	Yes

खरीदार परिभाषित अतिरिक्त विशिष्टता के लिए | Buyer Defined Additional Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric

Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 70 sq mm

विनिर्देश Specification	मूल्य Value
Conformity of the specification as per IS:1554 (Part 1):1988 latest	Agree
Identification on the cable as per Cl. 17 of IS:1554 (Part 1) latest Packing and marking as per Cl. 18 of IS:1554 (Part 1) latest	Agree
Conductor material (Complying with IS:8130:1984 latest)	Aluminium
Standard cable length on a drum : 250 meter (+/- 5%)	250 meter (+/- 5%)

Product Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 240 sq mm

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
GENERIC	Conformity of the specification	as per IS:1554 (Part 1):1988 latest
	BIS Marked	Yes for Type-A Insulation, Yes for Type-C Insulation
	BIS License Number (CM/L Number) - Must declare	8579810
	No. of core	4
	Nominal Area of Conductor (in Sq.mm)	240
CONSTRUCTION	Conductor material (Complying with IS:8130:1984 latest)	Aluminium
	Construction of Conductor	Stranded
	Type of Insulation	General purpose
	Type of PVC compound for insulation	Type - A
	Type of PVC compound for outer sheath	Type ST-1
	Filler and inner sheath	Thermoplastic materials
	Armouring	Galvanized steel formed wire (strip) armoured
	Improved fire performance category	1
MARKING	Identification on the cable	as per Cl. 17 of IS:1554 (Part 1) latest
	Packing and marking	as per Cl. 18 of IS:1554 (Part 1) latest
OPTIONAL TEST REPORTS	Availability of test reports for Cold bend test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Cold impact test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Armour resistance test (If reports available select 1, If reports not available select 0)	1
CERTIFICATIONS	Availability of Type test report with improved fire performance from Central government/NABL/ILAC accredited laboratory to prove the conformity of the specification	Yes with optional test reports
	Test report number - Must declare	INTERNAL REPORT
	Report date - Must declare	INTERNAL REPORT
	Name of lab - Must declare	INTERNAL REPORT
	Address of lab - Must declare	INTERNAL REPORT
	Agreed to furnish all the test reports and certification to buyer / consignee on demand	Yes

उत्पाद का बीआईएस लाइसेंस | BIS license of the product: 8579810

खरीदार परिभाषित अतिरिक्त विशेषता के लिए | Buyer Defined Additional Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 240 sq mm

विनिर्देश Specification	मूल्य Value
Identification on the cable as per Cl. 17 of IS:1554 (Part 1) latest Packing and marking as per Cl. 18 of IS:1554 (Part 1) latest	Agree
Conformity of the specification as per IS:1554 (Part 1):1988 latest	Agree
Standard cable length on a drum	250 meter (+/- 5%)
Conductor material (Complying with IS:8130:1984 latest)	Aluminium

Product Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 50 sq mm

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
GENERIC	Conformity of the specification	as per IS:1554 (Part 1):1988 latest
	BIS Marked	Yes for Type-A Insulation, Yes for Type-C Insulation
	BIS License Number (CM/L Number) - Must declare	2600640
	No. of core	4
	Nominal Area of Conductor (in Sq.mm)	50
CONSTRUCTION	Conductor material (Complying with IS:8130:1984 latest)	Aluminium
	Construction of Conductor	Stranded
	Type of Insulation	General purpose
	Type of PVC compound for insulation	Type - A
	Type of PVC compound for outer sheath	Type ST-1
	Filler and inner sheath	Thermoplastic materials
	Armouring	Galvanized steel formed wire (strip) armoured
	Improved fire performance category	1
	Construction of Conductor .	Stranded
MARKING	Identification on the cable	as per Cl. 17 of IS:1554 (Part 1) latest
	Packing and marking	as per Cl. 18 of IS:1554 (Part 1) latest
OPTIONAL TEST REPORTS	Availability of test reports for Cold bend test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Cold impact test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Armour resistance test (If reports available select 1, If reports not available select 0)	1
CERTIFICATIONS	Availability of Type test report with improved fire performance from Central government/NABL/ILAC accredited laboratory to prove the conformity of the specification	Yes with optional test reports
	Test report number - Must declare	internal report
	Report date - Must declare	internal report
	Name of lab - Must declare	internal report
	Address of lab - Must declare	internal report
	Agreed to furnish all the test reports and certification to buyer / consignee on demand	Yes

उत्पाद का बीआईएस लाइसेंस | BIS license of the product: 8579810

खरीदार परिभाषित अतिरिक्त विशिष्टता के लिए | Buyer Defined Additional Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 50 sq mm

विनिर्देश Specification	मूल्य Value
Identification on the cable as per Cl. 17 of IS:1554 (Part 1) latest Packing and marking as per Cl. 18 of IS:1554 (Part 1) latest	Agree
Standard cable length on a drum	250 meter (+/- 5%)
Conductor material (Complying with IS:8130:1984 latest)	Aluminium
Conformity of the specification as per IS:1554 (Part 1):1988 latest	Agree

Product Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 35 sq mm

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
GENERIC	Conformity of the specification	as per IS:1554 (Part 1):1988 latest
	BIS Marked	Yes for Type-A Insulation, Yes for Type-C Insulation
	BIS License Number (CM/L Number) - Must declare	8579810

	No. of core	4
	Nominal Area of Conductor (in Sq.mm)	35
CONSTRUCTION	Conductor material (Complying with IS:8130:1984 latest)	Aluminium
	Construction of Conductor	Stranded
	Type of Insulation	General purpose
	Type of PVC compound for insulation	Type - A
	Type of PVC compound for outer sheath	Type ST-1
	Filler and inner sheath	Thermoplastic materials
	Armouring	Galvanized steel strip armoured
	Improved fire performance category	1
	Construction of Conductor .	Stranded
MARKING	Identification on the cable	as per Cl. 17 of IS:1554 (Part 1) latest
	Packing and marking	as per Cl. 18 of IS:1554 (Part 1) latest
OPTIONAL TEST REPORTS	Availability of test reports for Cold bend test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Cold impact test (If reports available select 1, If reports not available select 0)	1
	Availability of test reports for Armour resistance test (If reports available select 1, If reports not available select 0)	1
CERTIFICATIONS	Availability of Type test report with improved fire performance from Central government/NABL/ILAC accredited laboratory to prove the conformity of the specification	Yes with optional test reports
	Test report number - Must declare	INTERNAL REPORT
	Report date - Must declare	INTERNAL REPORT
	Name of lab - Must declare	INTERNAL REPORT
	Address of lab - Must declare	INTERNAL REPORT
	Agreed to furnish all the test reports and certification to buyer / consignee on demand	Yes

खरीदार परिभाषित अतिरिक्त विशिष्टता के लिए | Buyer Defined Additional Specification for SBC General purpose PVC Insulated (Heavy Duty) Electric Cables, Aluminium Conductor - for Working Voltages Up to and including 1100 Volts with area 4 core 35 sq mm

विनिर्देश Specification	मूल्य Value
Conformity of the specification as per IS:1554 (Part 1):1988 latest	Agree
Conductor material (Complying with IS:8130:1984 latest)	Aluminium
Identification on the cable as per Cl. 17 of IS:1554 (Part 1) latest Packing and marking as per Cl. 18 of IS:1554 (Part 1) latest	Agree
Standard cable length on a drum	250 meter (+/- 5%)

ईपीबीजी विवरण | ePBG Detail

सलाहकार बैंक Advisory Bank :	State Bank of India
ईपीबीजी प्रतिशत (%) ePBG Percentage(%):	10.00
बोली लगाने वाले को बोली के नियमों और शर्तों के अनुसार लागू ईपीबीजी प्रस्तुत करना होगा The bidder shall furnish ePBG as applicable as per bid's terms and conditions	

नियम और शर्तें | Terms and Conditions

1. General Terms and Conditions-

- 1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

2. Buyer Added Bid Specific Terms and Conditions-

2.1 Scope of Supply:

Scope of supply (Bid price to include all cost components) : Only supply of Goods

2.2 Certificates:

Bidder's offer is liable to be rejected if they don't upload any of the certificates / documents sought in the Bid document, ATC and Corrigendum if any.

2.3 Buyer Added Bid Specific ATC:

Buyer uploaded ATC document [Click here to view the file.](#)

2.4 Generic:

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.

2.5 Generic:

Buyer Organization specific Integrity Pact shall have to be complied by all bidders. Bidders shall have to upload scanned copy of signed integrity pact as per Buyer organizations policy along with bid. [Click here to view the file.](#)

2.6 Generic:

Without prejudice to Buyer's right to price adjustment by way of discount or any other right or remedy available to Buyer, Buyer may terminate the Contract or any part thereof by a written notice to the Seller, if:

- i) The Seller fails to comply with any material term of the Contract.
- ii) The Seller informs Buyer of its inability to deliver the Material(s) or any part thereof within the stipulated Delivery Period or such inability otherwise becomes apparent.
- iii) The Seller fails to deliver the Material(s) or any part thereof within the stipulated Delivery Period and/or to replace/rectify any rejected or defective Material(s) promptly.
- iv) The Seller becomes bankrupt or goes into liquidation.
- v) The Seller makes a general assignment for the benefit of creditors.
- vi) A receiver is appointed for any substantial property owned by the Seller.
- vii) The Seller has misrepresented to Buyer, acting on which misrepresentation Buyer has placed the Purchase Order on the Seller.

2.7 Buyer Added Bid Specific ATC:

Buyer Added text based ATC clauses

The bidders are requested to refer the Buyer Added BID specific ATC file and submit the bid specific documents as per the formats provided

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.